

# BatLED



#### 6810-030-CR5

#### BatLED I30 4170lm 40W CR5

The BatLED is one of U-Tron's most versatile lighting solutions. It can be powered by both conventional and solar power supplies. U-Tron innovated the design of the typical halogen flood light and turned it into an eco-friendly system. The BatLED can be used as interior/exterior flood lights, and general purpose exterior lighting.

## Product Technical Data

## General Information Product Dimensions

Heatsink 6063-T5 aluminum alloy Lamp Length 284mm
Life Span 50000hr Lamp Width 333mm
Lamp Height 200.5mm

Lamp Height 200.5mm Lamp Body Length 284mm

#### Light Characteristics

Efficacy 104.25 lm/W

Beam Angle 120

CCT 5500K Ordering Information

Flux 4170lm Product Number A-6810-030-CR5
Color Rending 85 Product Name BatLED I 30

Index Product Ordering Name BatLED I 30 4170LM

CR5

Electrical CharacteristicsPieces Per Pack2Wattage40WPacks Per Carton2

Voltage universal Net Weight Per Piece 7.3Kg

Power Factor 0.937

## Temperature


Operating Temp. -40(min), 45(max)C Storage -40(min), 45(max)C

#### www.u-tron.com



# BatLED

## **Technical Drawing**



©2012 U-Tron (Beijing) Electronics Co., LTD All rights reserved Specifications are subject to change without notice



